



技术要求Specification:

- 1、材质Material: PA66 UL94V-2;
- 2、塑件表面平整光洁, 无明显的毛刺、气泡、变形、浇口拉伤、缺料等不良现象。

Plastic surface smooth and clean, no obvious burrs bubbles, distortion, gate strain, lack of material and other undesirable phenomena.

Part No	Pin	A	B
WAFER-ZH1.5-2PJK	2	1.50	3.30
WAFER-ZH1.5-3PJK	3	3.00	4.80
WAFER-ZH1.5-4PJK	4	4.50	6.30
WAFER-ZH1.5-5PJK	5	6.00	7.80
WAFER-ZH1.5-6PJK	6	7.50	9.30
WAFER-ZH1.5-7PJK	7	9.00	10.80
WAFER-ZH1.5-8PJK	8	10.50	12.30
WAFER-ZH1.5-9PJK	9	12.00	13.80
WAFER-ZH1.5-10PJK	10	13.50	15.30
WAFER-ZH1.5-11PJK	11	15.00	16.80
WAFER-ZH1.5-12PJK	12	16.50	18.30
WAFER-ZH1.5-13PJK	13	18.00	19.80
WAFER-ZH1.5-14PJK	14	19.50	21.30
WAFER-ZH1.5-15PJK	15	21.00	22.80
WAFER-ZH1.5-16PJK	16	22.50	24.30
WAFER-ZH1.5-17PJK	17	24.00	25.80
WAFER-ZH1.5-18PJK	18	25.50	27.30
WAFER-ZH1.5-19PJK	19	27.00	28.80
WAFER-ZH1.5-20PJK	20	28.50	30.30

MANUFACTURE DWG		东莞市讯普电子科技有限公司 DongGuan XunPu Electronics Co.,Ltd	
UNLESS OTHERWISE SPECIFIED TOLERANCES			TITLE: ZH1.5MM HOUSING
DECIMALS:	ANGLES:		PAR WAFER-ZH1.5-NPJK
.X±0.30	X.*±1°		DWN
.XX±0.20			CHKD
.XXX±0.10		APVD	SCALE 1:1 UNIT:MM
CUSTOMER COPY		SIZE:A4	UNIT:MM
		SHEET:1F1	REV:A