

Specifications:

Electrical:

- 1.Current Rating  
1.5A/contact terminal
- 2.Voltage Rating  
30V DC
- 3.Contact Resistance  
30 milliohms MAX
- 4.Dielectric Withstanding Voltage:  
500 V AC AT Sea Level
- 5.Insulation Resistance:  
1000MEGA ohms MIN

Mechanical:


- 1.Connector Mate and Unmate Force  
Mate force:3.75kgf (MAX)  
Unmate force:1.02kgf (MIN)
- 2.Terminal Retention 1.2kgf (MIN)

Material:

- 1.Housing:Hing Temperature Tnermaplastics,UL 94V-0 PBT/LCP White/Black
- 2.Contact:Copper Alloy C2680
- 3.Shell: Copper Alloy C2680/SPCC

Finish:

- 1.Contact: Plated Gold in Mating Area;Tin On Solder Talls
- 2.Shell: Nickel Plating



PCB.WELDING DRAWING (TOLERANCE:±0.05)

Pin Definition		
PIN	Signal Name	Describe
1	VBUS	+5V
2	D-	Neagative Data Channel
3	D+	Positive Data Channel
4	GND	Ground

MANUFACTURE DWG		东莞市讯普电子科技有限公司 DongGuan XunPu Electronics Co.,Ltd	
UNLESS OTHERWISE SPECIFIED TOLERANCES		TITLE: USB-AF-180°直脚13.0	
		PAR	USB-256-BRWH130
DECIMALS:	ANGLES:		DWN
X.X±0.30	X.*±5°		CHKD
X.XX±0.25	X.X*±1°		APVD
X.XXX±0.15			SCALE N:A
		CUSTOMER COPY	UNIT:MM SIZE:A4 SHEET:1F1 REV:A