



Part No	Pin	A	B	C
WAFER-254L-2P	2	2.50	10.00	7.50
WAFER-254L-3P	3	5.00	12.50	10.00
WAFER-254L-4P	4	7.50	15.00	12.50
WAFER-254L-5P	5	10.00	17.50	15.00
WAFER-254L-6P	6	12.50	20.00	17.50
WAFER-254L-7P	7	15.00	22.50	20.00
WAFER-254L-8P	8	17.50	25.00	22.50
WAFER-254L-9P	9	20.00	27.50	25.00
WAFER-254L-10P	10	22.50	30.00	27.50
WAFER-254L-11P	11	25.00	32.50	30.00
WAFER-254L-12P	12	27.50	35.00	32.50
WAFER-254L-13P	13	30.00	37.50	35.00
WAFER-254L-14P	14	32.50	40.00	37.50
WAFER-254L-15P	15	35.00	42.50	40.00
WAFER-254L-16P	16	37.50	45.00	42.50

NOTES:

- 1.BASE: LCP
- 2.PIN: Brass
- 3.Solder Tab: Brass

SPECIFICATIONS:

- 1.Spacing: 2.5
- 2.Voltage Rating: 250V AC DC
- 3.Current Rating: 3A AC DC
- 4.Insulation Resistance: 800MΩ Min
- 5.Contact Resistance: 20mΩ Max
- 6.Withstanding voltage: 1000V AC 1/Minute
- 7.Temperatuer Range: -25℃ ~+ 85℃

MANUFACTURE DWG		东莞市讯普电子科技有限公司 DongGuan XunPu Electronics Co.,Ltd	
UNLESS OTHERWISE SPECIFIED TOLERANCES			TITLE: WAFER 2.54 立贴
			PAR WAFER-254L-NP
			DWN
			CHKD
DECIMALS:	ANGLES:		
X.:±0.2	X':.:±5°		
.X:±0.1	X.X':.:±3°		
.XX:±0.05	X.XX':.:±1°		
CUSTOMER COPY		SCALE:1:1	UNIT:MM
		SIZE:A4	SHEET:1F1
			REV:A