



备注(NOTE):

- 1. 材质:
 - 1.1 胶芯: LCP UL94 V-0
 - 1.2 端子: C2680, T=0.2mm: 镍底, 镀金
 - 1.3 外壳: 不锈钢201-H 表面镀镍
- 2. 电气特性:
 - 2.1 接触区: 接触电阻40mΩ Max, 允许10mΩ变化量. 测试条件: 20mv, 100mA下测量.
 - 2.2 接触电流: 3A VBUS引脚; 1.25A用于GND引脚; 其他引脚为0.25A.
 - 2.3 额定电压: 5V.
 - 2.4 耐电压: 100VAC.
 - 2.5 绝缘电阻: 至少100兆欧.
- 3. 机械性能:
 - 3.1 插入力: 0.5-2.0Kg
 - 3.2 拔出力: 0.6-2.04Kg
 - 3.3 插拔次数: 5000次.
- 4. 工作环境: -20℃ to +85℃.

USB TYPE C PIN ASSIGNMENTS

PIN NUMBER	SIGNAL NAME	PIN NUMBER	SIGNAL NAME
		B12	GND
		B9	VBUS
A5	CC1	B5	CC2
A9	VBUS		
A12	GND		

TABLE:

NO	PART	Q'TY	Material
1	SHELL	1	ZINC ALLOY, NI30u"Min PLATED
2	CONTACT	6	C2680, TIN80u"/Au1u"/NI30u" PLATED
3	1MD HOUSING	1	LCP UL94 V-0 BLACK
4	CAP	1	LCP UL94 V-0 BLACK
5	WATERPROOF RING	1	SILICONE UL94 V-0 BLACK

MANUFACTURE DWG

UNLESS OTHERWISE SPECIFIED TOLERANCES

DECIMALS: .X:±0.30 .XX:±0.20 .XXX:±0.10

ANGLES: X':±10.0' X.X':±8.0'

CUSTOMER COPY

东莞市讯普电子科技有限公司
DongGuan XunPu Electronics Co., Ltd

TITLE: TYPE CF 6P 直插15.0 3A 不锈钢 盒装

PAR TYPE-C-903-LDRP6

DWN

CHKD

APVD

SCALE: 1:1 UNIT: MM

SIZE: A4 SHEET: 1F1 REV: A