



PCBLAYOUT  
TOL:±0.05

NOTES

MATERIAL

- 1.HOUSING MATERIAL: GLASS FILLED POLYESTER UL94V-0.
- 2.CONTACT MATERIAL: PHOSPHOR BRONZE ∅0.46mm.
- 3.PLATING: GOLD FLASH PLATING OVER NICKEL.

ELECTRICAL

- 1.VOLTAGE RATING: 125 VAC RMS.
- 2.CURRENT RATING: 1.5 AMP.
- 3.CONTACT RESISTANCE: 40 MILLIOHMS MAX.
- 4.INSULATION RESISTANCE: 500 MEGOHMS MIN @ 100V DC

5.DIELECTRIC DIELECTRIC

RESISTANCE: 500V DC RMS 50Hz. 1MIN.

MECHANICAL

- 1.DURRABILITY: 750 CYCLES MIN.
2. MATING/UNMATING FORCE: 2.24 KG.F MAX.

ENVIRONMENTAL:

- 1.STORAGE: -40℃~+85℃.
- 2.OPERATION: -40℃~+85℃.

PART NUMBER DESCRIPTION:

RJ45-541-003-XX

流水码  
21:全塑无灯GF PBT黑盘装  
22:全塑无灯GF PBT黄盘装

MANUFACTURE DWG		 东莞市讯普电子科技有限公司 DongGuan XunPu Electronics Co.,Ltd	
UNLESS OTHERWISE SPECIFIED TOLERANCES			TITLE: 5623 1X4全塑无灯DIP
			PAR RJ45-541-003-21
			DWN
			CHKD
DECIMALS: .X:±0.35 .XX:±0.25 .XXX:±0.15	ANGLES: X':±3' .X':±2' .XX':±1'	APVD	SCALE:1:1
		CUSTOMER COPY	UNIT:MM
			SIZE:A4
			SHEET:1F1
			REV:A