



RECOMMENDED PCB LAYOUT
GENERAL TOLERANCE ±0.05

Technical requirements	
Characteristic impedance	50Ω
Frequency range	6GHz
Contact resistance	
Inner conductor	≤5mΩ
Outer conductor	≤1mΩ
Standing ratio	
Standing Wave Ratio	1.1+0.02f(GHz)
Withstand voltage	750V/50Hz
Insulated resistance	≥1000MΩ
Appearance: no shift point burr scratch surface bright, no dirt, no deformation, etc	

1	整体外壳	1	黄铜	镀金
2	绝缘体	2	PTFE	
3	母针	1	铍铜	镀金
序号	名称	数量	材料	备注

MANUFACTURE DWG		 东莞市讯普电子科技有限公司 DongGuan XunPu Electronics Co.,Ltd	
UNLESS OTHERWISE SPECIFIED TOLERANCES		TITLE: MMCX-弯头插板母座-整体外壳 PAR: MMCX-KWE-351-H6.8X6.5 DWN: Lucas CHKD: Ethan APVD: Jacob SCALE: 1:1 UNIT: MM SIZE: A4 SHEET: 1F1 REV: A	
DECIMALS:	ANGLES:		
X.: ±0.10			
X.X: ±0.05			
X.XX: ±0.02			
CUSTOMER COPY			